Mobilt

temporary fence panels

The Mobilt system consists of galvanized mesh panels, an accessories system and stabilizing feet.

It is utilized in areas undergoing construction or roadwork, where hoarding fences are unnecessary.







easy assembly and disassembly



solid and durable construction



a wide range of fence types and accessories



anti-corrosion by galvanization



great protection of construction sites



check out the full range of our Mobilt fences

┓╸╻╴┎╴▫



| Panel type | Index | Dimensions [mm] | Weight [kg]* | Additional Reinforcement | Mesh eye [mm] | Wire diameter [mm] |
|------------------------|-------------|--------------------|-----------------|---|------------------|-----------------------|
| Mobilt | OT-MOB-M1 | 3430 × 2000 | 11 | no | 120 × 250 | 3,0 |
| Mobilt S | OT-MOB-M2 | 3430 × 2000 | 13 | additional horizontal pipe | 120 × 250 | 3,0 |
| Mobilt CB | OT-MOB-M3 | 3430 × 2000 | 11 | corner reinforcement | 120 × 250 | 3,0 |
| Mobilt PRO | OT-MOB-P1 | 3430 × 2000 | 14,5 | no | 120 × 250 | 3,0 × 4,0 |
| Mobilt HDG-3 | OT-MOB-HDG1 | 3430 × 2000 | 16 | no | 120 × 250 | 3,0 |
| Mobilt RC | OT-MOB-RC1 | 3430 × 2000 | 12 | no | 120 × 250 | 3,0 |
| Mobilt RC-CB | OT-MOB-RC3 | 3430 × 2000 | 12 | corner reinforcement | 120 × 250 | 3,0 |
| Mobilt RC-CBS | OT-MOB-RC4 | 3430 × 2000 | 14 | corner reinforcement, additional horizontal pipe | 120 × 250 | 3,0 |
| Mobilt Anti-Climb | OT-MOB-M6 | 3430 × 2000 | 16,5 | no | 40 × 250 | 3,0 |
| Mobilt RC-S Anit-Climb | OT-MOB-RC8 | 3430 × 2000 | 19 | additional horizontal pipe | 40 × 250 | 3,0 |
| Mobilt H-RC | OT-MOB-H2 | 3430 × 1200 | 8,8 | no | 120 × 250 | 3,0 |
| MOBILT H | OT-MOB-H1 | 3430 × 1200 | 7,8 | no | 120 × 250 | 3,0 |

*The actual weight of the products may differ from the stated value by up to 5%, as the applicable standards (e.g. EN 10305-3 for tubes, EN 10218-2 for wire, EN 10346 for sheet metal) allow specific dimensional tolerances that directly affect the weight of the final product.